

# Material Safety Data Sheet

## Section I - Product Identification

Product Name: Fass-Stripe Plus (Yellow)  
Manufacturer's Name: Maintenance, Inc.  
Address: PO Box 408, Wooster, Ohio 44691  
Phone Number: 330-264-6262 (Maintenance Inc.)  
Formula: FSPY-1  
Effective Date: 11-30-06  
Date Superseded: 04-05-04

## Section II - Hazardous Ingredients

### AZO Pigment

CAS# 61827-75-6  
% by wt. 1-5%  
Listed in SARA Title III, Section 313: No  
OSHA PEL: N/A  
ACGIH TLV: N/A  
LC50: N/A  
LD50: N/A

### Limestone

CAS# 1317-65-3  
% by wt. 50-55%  
Listed in SARA Title III, Section 313: No  
OSHA PEL: 5 mg/m<sup>3</sup> (dust)  
ACGIH TLV: 2 mg/m<sup>3</sup> (dust)  
LC50: N/A  
LD50: N/A

### Methanol

CAS# 67-56-1  
% by wt. 1-3%  
Listed in SARA Title III, Section 313: Yes  
OSHA PEL: 260 mg/m<sup>3</sup>  
ACGIH TLV: 328 mg/m<sup>3</sup>  
STEL: 250 ppm  
LC50: Inhalation, rat 64,000 ppm  
LD50: Ingestion, rat 5,628 mg/kg  
Absorption, rabbit 15,800 mg/kg

### Texanol Ester Alcohol

CAS# 25265-77-4  
% by wt. 0-2%  
Listed in SARA Title III, Section 313: No  
OSHA PEL: Not Established  
ACGIH TLV: Not established  
LC50: Inhalation, rat >2.75 mg/L/6 hours  
LD50: Ingestion, rat 3,200 mg/kg  
Absorption, rabbit 15,200 mg/kg

### Titanium Dioxide

CAS# 13463-67-7  
% by wt. 1%  
Listed in SARA Title III, Section 313: No  
OSHA PEL: 15 mg/m<sup>3</sup> (dust)  
ACGIH TLV: 10 mg/m<sup>3</sup> (dust)

## Section II - Nonhazardous Ingredients

### Water

CAS# 7732-18-5  
% by wt. >3

### Acrylic Latex

CAS# Proprietary  
% by wt. >3

N/A = Not available or applicable

Ingredients total wt. % are below 100% only if all others unlisted are not considered hazardous by any federal (OSHA, WHMIS, SARA), any state or province, or local Right-To-Know regulations.

### Section III - Physical Data

Boiling Point (degrees F/C): >212°F (100°C)  
Vapor Pressure (mm Hg.): Nearly equal to vapor pressure of water  
Vapor Density (Air = 1): <1  
Solubility in Water: Miscible  
Appearance and Odor: Yellow paint with slight ammonia odor.  
Physical State: Liquid  
Freeze Point (degrees F/C): 32°F (0°C)  
Specific Gravity: 1.6 – 1.7  
Evaporation Rate (Butyl Acetate = 1): ~1.8  
pH: N/A  
VOC: <150 grams per liter VOC

### Section IV - Fire & Explosion Hazard Data

Classification: N/A  
Flash Point (method used): Undetermined  
Flammable Limits: LEL: N/A      UEL: N/A  
Combustion Products: Smoke, fumes, CO, CO<sub>2</sub> and traces of monomer as well as toxic pyrolysis products.  
Extinguishing Media: Foam, dry chemical, CO<sub>2</sub>, water fog.  
Special Fire Fighting Procedures: Cool exposed containers to prevent steam pressure buildup. Wear self-contained breathing equipment.  
Unusual Fire and Explosion Hazards: Containers may rupture due to steam pressure.  
HMIS Rating: Health 1;      Fire 0;      Reactivity 0  
Impact Sensitive: No  
Static Sensitive: No  
Explosion Power: N/A  
Burning Rate: N/A

### Section V - Health Hazard Data

Routes of Entry: Eyes, inhalation, ingestion.  
Effect of Overexposure:  
Eyes: Vapor and liquid may cause eye irritation.  
Inhalation: Excess inhalation may cause irritation to nose and throat, dizziness, giddiness, nausea, and headache.  
Skin: May cause irritation. May cause allergic reaction in some people.  
Ingestion: May be harmful if swallowed. Ingestion causes nausea, cramps, vomiting and diarrhea.  
Unusual Chronic Toxicity: Prolonged and repeated inhalation may cause damage to kidneys, liver, blood or central nervous system. Repeated ingestion may cause liver damage.  
Any Suspected Carcinogen >or= 0.1%: No  
Emergency and First Aid Procedures:  
Eyes: Immediately flush with plenty of water for 15 minutes and call a physician.  
Inhalation: If affected, remove to fresh air, administer oxygen and call physician.  
Skin: Wash thoroughly with plenty of water and soap.  
Ingestion: If vomiting begins, keep head below hips to avoid aspiration into lungs. Seek physician immediately, show MSDS or label. Give 1-2 glasses of water or milk. DO NOT induce vomiting.

## Section VI - Reactivity Data

Stability: Stable

Conditions to Avoid: Keep from freezing and extreme heat.

Incompatibility (materials to avoid): Strong acids or bases, catatonic emulsions or multivalent salts (e.g. magnesium or calcium salts) will cause coagulation.

Hazardous Decomposition Products: N/A

Hazardous Polymerization: Will not occur.

## Section VII - Spill or Leak Procedures

SARA Title III:

#302: No    #304 CERCLA: No    #313: No

Steps to be Taken In Case Material is Released or Spilled: Contain the spill. If ventilation is inadequate, wear approved respiratory protection. Wear suitable protective clothing, gloves, and eye/face protection. Clean up with absorbent materials. Put in a sealed approved container. Dispose of in accordance with federal, state and local regulations.

## Section VIII - Safe Handling & Protection Information

Respiratory Protection: If ventilation is inadequate, wear approved respiratory equipment. If spray applied, wear approved respiratory protection.

Ventilation:

Local Exhaust: Recommended

Mechanical (general): Recommended

Special: N/A

Other: N/A

Protective Gloves: Wear impervious gloves.

Eyes Protection: Wear safety glasses, goggles or face shield.

Other Protective Equipment: Wear suitable protective clothing.

Estimated LD50, MG/KG: N/A

Estimated: LC50, MG/KG: N/A

Sensitization: No

Irritant: No

## Section IX - Special Precautions

Keep out of reach of children.

For professional and industrial use only.

Always read label plus precautions and follow directions carefully.

Keep from freezing.

Keep containers air tight for storage.

Avoid breathing vapor or spray mist.

Avoid contact with eyes and skin.

Do not take internally.

Wash thoroughly after using.

Additional Technical Data Sheets and/or MSDS's are available upon request.

THE INFORMATION AND RECOMMENDATION PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND MAINTENANCE INC DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.