



COLOR COAT (LIGHT GREEN)

Material Safety Data Sheet - OSHA 174

May be used to comply with OSHA's Hazard communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

US Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Section I. Manufacturer/Product Information

Manufacturer's Name: Maintenance, Inc.
Address: PO Box 408 Wooster, OH 44691
Phone Number: 330-264-6262 (Maintenance, Inc.)
Emergency Phone Number: 1-800-424-9300

H.M.I.S. Rating

Health	1
Flammability	0
Reactivity	0
Protective Equip.	E

Section II. Chemical Composition

Ingredient	CAS #	OSHA PEL	ACGIH TLV	Other Limits	Percent
Acrylic Polymer	Proprietary	N/A	N/A		
Coalescent	25265-77-4	N/A	N/A		
Ethylene Glycol	107-21-1	100mg/m ³	100mg/m ³		
Silica	60676-86-0	10mg/m ³	.025mg/m ³		
Chromic Oxide	1308-38-9	0.5mg/m ³	0.5mg/m ³		

Section III. Physical Data

Physical State: Liquid
Freeze Point: (Liquid) 32° F
Boiling Point: 100° Celsius (212° Fahrenheit)
Specific Gravity (H₂O=1): 1.13
Melting Point: N/A
Vapor Pressure (mm Hg): Nearly equal to water
Vapor Density (AIR = 1): <1
Evaporation Rate (Butyl Acetate = 1): Approximately 1.8
Solubility in Water: Easily dispersible in the liquid state
Appearance and Odor: Green liquid, mild odor

Section IV. Fire & Explosion Hazard Data

Impact Sensitive: No **Static Sensitive:** No **Explosion Power:** N/A **Burning Rate:** N/A
Flash Point (Method Used): N/A **Flammable Limits:** N/A **LEL:** N/A **UEL:** N/A
Extinguishing Media: Foam, CO₂, dry chemical, water fog, other
Special Fire Fighting Procedures: Full protective equipment, including self-contained breathing apparatus to be worn. Water cool sealed containers in area of fire to prevent rupture due to steam generation.
Unusual Fire and Explosion Hazards: N/A

Section V. Health Hazard Data

Routes of Entry: Eyes, Inhalation, Ingestion
Effect of Overexposure: May cause eye irritation. May cause skin irritation. Excess inhalation of vapors may cause respiratory irritation, dizziness, weakness, fatigue, nausea, headache. Overexposure can cause neurological damage. Ingestion causes nausea, cramps, vomiting, diarrhea or gastrointestinal irritation. **NOTE:** Contains encapsulated silica-crystalline. Normal product usage should not result in respirable dust that would be hazardous to the respiratory system. **WARNING:** This product contains a chemical known to the State of California to cause cancer.
Any Suspected Carcinogen > or = 0.1%: No

Section V. Health Hazard Data (Continued)

Emergency First Aid Procedures:

Eyes: Immediately flush with plenty of water for 15 minutes and call a physician.

Inhalation: If affected, remove to fresh air.

Skin: Wash thoroughly with plenty of water and soap. Remove contaminated clothing and launder before reuse.

Ingestion: Seek a physician immediately, show MSDS or label. DO NOT induce vomiting. If conscious, give 1-2 glasses of water.

Section VI. Reactivity Data

Stability: Stable

Conditions to Avoid: Keep from freezing and extreme heat

Incompatibility (Materials to Avoid): Strong oxidizing agents, acids, and selected amines

Hazardous Decomposition of Byproducts: Thermal decomposition may yield CO and CO₂.

Hazardous Polymerization: Will not occur

Conditions to Avoid: N/A

Section VII. Spill Procedures

SARA Title III:

#302: No **#304 CERCLA:** No **#313:** See Section II

Steps to be Taken in Case Material is Released or Spilled: Ventilate the area. Wear suitable protective clothing, gloves, and eye/face protection. Clean up with absorbent material. Put in a sealed approved container. Dispose of as a non-hazardous waste in accordance with federal, state, and local regulations.

Section VIII. Safe Handling & Protection Information

Respiratory Protection: Use only in well ventilated areas. If ventilation is inadequate, wear approved respiratory equipment.

Ventilation-

Local Exhaust: Recommended **Mechanical (General):** Recommended **Special:** N/A **Other:** N/A

Protective Gloves: Wear protective gloves

Eye Protection: Wear safety glasses, goggles, or face shield

Other Protective Equipment: N/A

Estimated LD50, MG/KG: N/A

Estimated LC50, MG/KG: N/A

Sensitization: No **Irritant:** N/A

Section IX. Special Precautions

Keep out of reach of children. For professional and industrial use only. Always read label plus precautions and follow directions carefully. Keep from freezing. Avoid contact with eyes, skin, and clothing. Wear suitable protective clothing, gloves and eye/face protection. Wash thoroughly after using. Do not breathe vapor or spray mist. Use only in well ventilated areas. Keep containers closed when not in use. DO NOT TAKE INTERNALLY.

Section X. Disclaimer

The information and recommendation provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and Maintenance, Inc. disclaims any and all liability or legal responsibility for use or reliance upon same.



MAINTENANCE, INC.

P.O. BOX 408 • WOOSTER, OH 44691

CALL TOLL FREE: 1-800-892-6701 • FAX TOLL FREE: 1-800-264-2578
WEBSITE: www.maintinc.com

Specialists in Pavement Maintenance Since 1938