



ACRYLIC POURABLE CRACK FILLER

Product Name

REC-TECH Acrylic Pourable Crack Filler

Manufacturer

Maintenance, Inc.
P.O. Box 408
Wooster, OH 44691
1-800-892-6701
www.maintinc.com

Product Description

REC-TECH Acrylic Pourable Crack Filler is a 100% acrylic elastomeric liquid crack sealer that has outstanding low-temperature flexibility and elasticity. It is designed for use in cracks up to 1/2" wide in asphalt or concrete recreational surfaces.

Uses

This product is designed as a crack filler for use on asphalt or concrete sports surfaces.

Color Availability

REC-TECH Acrylic Pourable Crack Filler is available in green, red, and neutral.

Preparation of Surface

Cracks should be cleaned completely of dirt, loose stone, and vegetation before application.

Application

Fill crack with Acrylic Pourable Crack Filler directly from jug. Do not dilute. Fill deep cracks first with backer rod or dry sand to within 3/4" of surface. Keep material at or below surface level. Use a rubber squeegee to scrape off any excess.

Weather Conditions

Temperature must be at least 50°F and rising during application and for at least 24 hours after application. Do not apply if rain is imminent or forecast for the next 24 hours.

Drying Time

Drying time is dependent upon weather conditions and thickness of application.

Coverage

Acrylic Pourable Crack Filler will fill approximately 75-150 linear feet per gallon of cracks depending upon depth and width of cracks.

Clean Up

Wash tools with soap and water before material has dried.

VOC

Less than 100 grams of volatile organic compounds per liter.

Precautions

**KEEP OUT OF REACH OF CHILDREN.
PROTECT FROM FREEZING.**

Do not take internally. **If swallowed**, call a physician immediately. **In case of eye contact**, flush immediately with water for 15 minutes and call a physician. Do not store in direct sunlight or at temperatures above 100°F. **In case of spillage**, absorb and dispose of in accordance with Federal, State, and local regulations. When not in use, keep containers tightly closed and upright to prevent leakage.

Product Data

Type	Acrylic Emulsion
Pounds Per Gallon at 77 °F	8.85 +/- .5
Odor	Slight Ammonia
Flammability	Non-Flammable
Flash Point	None

Copyright © 2009 Maintenance, Inc.
All Rights Reserved

www.maintinc.com



MAINTENANCE, INC.
P.O. BOX 408 • WOOSTER, OH 44691

CALL TOLL FREE: 1-800-892-6701 • FAX TOLL FREE: 1-800-264-2578
WEBSITE: www.maintinc.com

Specialists in Pavement Maintenance Since 1938