



ACRYLIC RESURFACER

Product Name

REC-TECH Acrylic Resurfacer

Manufacturer

Maintenance, Inc.
P.O. Box 408
Wooster, OH 44691
1-800-892-6701
www.maintinc.com

Product Description

REC-TECH Acrylic Resurfacer, applied to asphalt or concrete surfaces, fills surface voids and imperfections and helps provide a smooth, well prepared surface. This 100% acrylic emulsion is designed for onsite mixing with silica sand and water.

Uses

Product is designed to prepare asphalt and concrete sports surfaces for REC-TECH Concentrate Color.

Color Availability

REC-TECH Acrylic Resurfacer is available in neutral and black.

Preparation of Surface

Pavement surface should be cleaned completely of dirt, loose stone, and vegetation before application. All cracks and low spots should be repaired and smoothed prior to application.

Allow newly applied asphalt to cure for at least one month prior to applying REC-TECH Acrylic Resurfacer.

Mixing Directions

Patching Material - For Use on Lifts up to 1/4"

Acrylic Resurfacer	10 Gallons
Water	5 Gallons
Sand	200 Lbs. (30-40 Mesh AFS)
Cement	1/2 Gallons

(Combine Cement and a small amount of Water before adding to Patching Material Mix)

Coating Material Use

Acrylic Resurfacer	55 Gallons
Water	33 Gallons
Sand	800 Lbs. (50-70 Mesh AFS)

Application

Mix Acrylic Resurfacer according to directions and apply with a rubber squeegee. Material should be stirred thoroughly before use. Smooth all rough spots before the application of additional coats.

Weather Conditions

Temperature must be at least 50°F and rising during application and for at least 24 hours after application. Do not apply if rain is imminent or forecast for the next 24 hours.

Drying Time

Allow each coat of Acrylic Resurfacer to dry completely between coats.

Coverage

Coverage is approximately .07 to .09 gallons per square yard, per coat. Coverage is based on undiluted gallons of Acrylic Resurfacer and will vary according to the porosity and texture of the surface.

Clean Up

Wash tools with soap and water before material has dried.

VOC

Less than 100 grams of volatile organic compounds per liter.

Precautions

**KEEP OUT OF REACH OF CHILDREN.
PROTECT FROM FREEZING.**

Do not take internally. **If swallowed**, call a physician immediately. **In case of eye contact**, flush immediately with water for 15 minutes and call a physician. Do not store in direct sunlight or at temperatures above 100°F. **In case of spillage**, absorb and dispose of in accordance with Federal, State, and local regulations. When not in use, keep containers tightly closed and upright to prevent leakage.



ACRYLIC RESURFACER

Rev. 5/09

Product Data

Type	Acrylic Emulsion
Pounds Per Gallon at 77 °F	8.5 +/- .5
Odor	Slight Ammonia
Flammability	Non-Flammable
Flash Point	None

Copyright © 2009 Maintenance, Inc.
All Rights Reserved

www.maintinc.com

REC-TECH ACRYLIC RESURFACER



MAINTENANCE, INC.
P.O. BOX 408 • WOOSTER, OH 44691

CALL TOLL FREE: 1-800-892-6701 • FAX TOLL FREE: 1-800-264-2578
WEBSITE: www.maintinc.com

Specialists in Pavement Maintenance Since 1938

Form No. RT02